


# Orvito Home Intelligence<sup>TM</sup>



#### Solution Overview

An Enhanced Experience — secure, convenient and luxurious!

It is the only smart home automation solution available today that offers complete integration of lighting, security and safety to offer you a truly connected home. Now stay connected to your space remotely through a hassle-free, flexible and modular wireless network.

# Key Features

- ▶ Appliance and light control
- Mood lighting and preset scenes
- > Visitor management and live video surveillance
- » Media and entertainment unit control
- Based on open standards the solution is scalable and flexible to let you add as many other products.
- No costly changes to network infrastructure
- ► Energy analytics to reduce your carbon footprint
- > Remote monitoring and control through Orvito Cloud
- > Customizable and unified app to control and monitor all your devices
- ▶ Installation time of less than 20 mins

Control anytime, anywhere.....



#### Smart Switch Panel™

Minimalistic Design, Technology Driven.

Smart Switch Panel™ allows the user to efficiently control lighting, appliances, blinds/curtains and preset scenes. The panel has an ability to trigger a preset scene or alert you while you are away.

#### Features

- Single-touch control of appliances
- Wireless control from iOS and Android smartphones & tablets
- Remote control through Orvito Cloud

	5 A on/off	5 A dimmer	16 A on/off
OV-WI-SP4-01-220	0	2	2
OV-WI-SP6-01-220	5	1	0
OV-WI-SP6-02-220	4	2	0
OV-WI-SP8-01-220	7	1	0
OV-WI-SP8-02-220	6	2	0
Manual: Touch-base	ed		
Remote: Through S	Smartphone/Ta	ablet/Orvito C	loud using
ОНІ™ арр	s or Orvito Clo	oud account	
Wi-Fi®			
85-265 V AC, 50/60	Hz		
Standard 4 switch, 6 switch & 8 switch panel sizes			
Operating Temperature: -40° C to +70° C			
OHI™ Platform 1.0			
FCC, IC, WPC, CE			
Fire retardant, shock	k resistant		
	OV-WI-SP6-01-220 OV-WI-SP6-02-220 OV-WI-SP8-01-220 OV-WI-SP8-01-220  Manual: Touch-base Remote: Through S OHI™ app Wi-Fi® 85-265 V AC, 50/60 Standard 4 switch, G Operating Tempera	OV-WI-SP4-01-220       0         OV-WI-SP6-01-220       5         OV-WI-SP6-02-220       4         OV-WI-SP8-01-220       7         OV-WI-SP8-02-220       6         Manual: Touch-based         Remote: Through Smartphone/Ta         OHI™ apps or Orvito Clowi-Fi®         85-265 V AC, 50/60 Hz         Standard 4 switch, 6 switch & 8 stores         Operating Temperature: -40° C to         OHI™ Platform 1.0	OV-WI-SP4-01-220       0       2         OV-WI-SP6-01-220       5       1         OV-WI-SP6-02-220       4       2         OV-WI-SP8-01-220       7       1         OV-WI-SP8-02-220       6       2         Manual: Touch-based       Remote: Through Smartphone/Tablet/Orvito C         OHI™ apps or Orvito Cloud account       Wi-Fi®         85-265 V AC, 50/60 Hz       Standard 4 switch, 6 switch & 8 switch panel si.         Operating Temperature: -40° C to +70° C         OHI™ Platform 1.0         FCC, IC, WPC, CE



## Video Door Phone

Where Technology meets Art......

Elegant, affordable and real time visibility into what's happening at your door. This intelligent piece of hardware is equipped with a microphone and camera. With HD resolution and built-in night vision you can rely on clear video quality around the clock.

#### Features

- Two way audio, one way video communication with single touch UI that enables resident to easily converse with visitor
- Infrared (IR) camera on the outdoor unit to provide clear images of visitor

Part Number	Outdoor Unit: OV-WI-VDP-01-220
	Indoor Unit: OV-WI-VDP-02-220
Indoor Unit	Display: Apps installable on any iPad or Android tablet
	to create multiple indoor units
	Power Input: 5 V AC-DC adapter
	Talk Time: Unlimited
	Monitoring Time: Unlimited
Outdoor Unit	Camera Resolution: 5 MP
	Dimension: 88 mm x 146 mm x 32 mm (Width x Height x Depth)
	Power Input: 85-265 V AC, 50/60 Hz
	Power Consumption: Less than 8 W
Installation Method	Outdoor Unit: Surface mounted
Communication	Wi-Fi®
Environmental	Operating Temperature: -40° C to +70° C
Requirements	
Software	OHI™ Video Door Phone 1.0
Certifications	FCC, IC, WPC



#### Indoor Surveillance Camera

With real time surveillance, keep an eye on your premises at all times. The wide angle capture and pan, tilt & zoom feature of the indoor camera improves the overall surveillance of your property. The discreet design, high quality, reliability and ease of installation make Orvito's Indoor Video Surveillance Camera an obvious choice!

#### Features

- Wi-Fi® cameras with HD video output (720p)
- Pan, tilt & zoom control feature with in-built motion sensor
- Low-light/night viewing capability to provide 24-hour surveillance
- Remote viewing from outside home without need for fixed IP address
- Programmable to record in continuous mode, or based on motion/time
- Record and store video feed wirelessly (requires Orvito Smart Hub)

Part Number	OV-WI-OCM-01-220
Communication	Wi-Fi <sup>®</sup>
Power Inputs	5 V AC-DC adaptor
Dimensions	Length: 20 mm
	Width: 120 mm
	Height: 180 mm
	Weight: 600 g
Video	Resolution: 1280 x 720 p
	Support up to 25 fps
PTZ	Pan, Tilt and Zoom
Night Vision	Infrared IR - Cut LED
	Distance: 10 m
Software	OHI™ Platform 1.0
Certifications	FCC, IC



## Outdoor Surveillance Camera

Protect your property with this high-quality, wireless outdoor security camera that records and archives video feed. Orvito Outdoor Video Surveillance Camera is designed to withstand harsh weather conditions and provide reliable surveillance at all times.

#### Features

- Wi-Fi® weatherproof cameras
- In-built motion sensor
- Low-light/night viewing capability to provide 24 hour surveillance
- Remote viewing from outside home without need for fixed IP address
- Can record in continuous mode, or based on motion/time
- Record and store video feed wirelessly (requires Orvito Smart Hub)

Part Number	OV-WI-OCM-01-220
Communication	Wi-Fi®
Power Inputs	12 V AC-DC adapter
Dimensions	Length: 155 mm
	Width: 82 mm
	Height: 80 mm
	Weight: 725 g
Video	Resolution: 640 x 480 (VGA), 320 x 240 (QVGA)
	Support up to 25 fps
Night Vision	Infrared (IR)
	Distance: 20 m
Software	OHI™ Platform 1.0
Certifications	FCC, IC
Casing	Weatherproof



## Smart Hub

Orvito Smart Hub is the central unit that acts like a brain to power Orvito's automation solutions and also acts as a gateway to Orvito Cloud. Its small form factor allows the Smart Hub to be placed discreetly in any corner of the room. The Smart Hub requires Wi-Fi® coverage which can be provided through any IEEE 802.11 b/g/n compliant router.

#### Features


- Enables remote monitoring/control of appliances through Orvito Cloud
- Enables installation/control of smart switch panels and surveillance cameras
- Provides energy analytics and predictive billing features
- A single Smart Hub can enable automation for the entire house

OV-WI-HUB-01-220
5 V AC-DC adapter
120 mm x 37.5 mm x 91 mm
(Width x Height x Depth)
Ethernet, Wi-Fi® (IEEE 802.11 b/g/n)
Modular Storage with capacity starting from 320 gb
Operating Temperature: -40° C to +70° C
OHI™ Platform 1.0
FCC, IC, CE




# Dynamic User Interface

All the Orvito products can be configured and controlled from a common user interface which is made available on web browser, smartphone and tablet (iOS and Android). Now you can control and interact with all your appliances, cameras and VDP from the same application. This user friendly interface can be personalized without any requirement of a system specialist or the need to call for technical services.



## Architecture



#### USA

Orvito, Inc.

303 Wyman Street, Suite 300, Waltham, MA 02451 USA.

Phone: 1-(781) 577-6646

Toll free: 1-(855) 467-8486 (1 855 4ORVITO)

Web: www.orvito.com | Email: info@orvito.com

Follow us: f /Orvito /OrvitoNews in /company/orvito-inc-